

PRICE LIST
Valid from 10 - Marzo 2008
International Rev. 1.03

- 1 ACCESSORIES
- 2 Analog I/O - S. Eur.
- 3 Analog I/O - BLOCK.
- 4 Analog I/O - M TYPE
- 5 AXIS Controls
- 6 B U S
- 7 B U S - BLOCK
- 8 C P U - Single Eur.
- 9 C P U - BLOCK
- 10 C P U - 3 TYPE
- 11 C P U - 4 TYPE
- 12 C P U - M TYPE
- 13 C P U - grifo® Analog BLOCK TYPE
- 14 C P U - grifo® Mini BLOCK TYPE
- 15 C P U - QG TYPE
- 16 C P U - C A N grifo® Mini Module
- 17 C P U - grifo® Mini Module TYPE
- 18 COMMUNICATIONS
- 19 Digital I/O - S. Eur.
- 20 Digital I/O - BLOCK
- 21 Digital I/O - Expan.
- 22 F B C
- 23 G M T - grifo® ModBUS Telecontrol
- 24 KEYBOARDS
- 25 KITs and Educationals
- 26 MASS MEMORIES
- 27 PC Interfaces
- 28 POWER Suppliers
- 29 Q T P - Pannelli Operatore (Quik Terminal Panel)
- 30 TELECONTROL
- 31 VIDEO Units

NAME	TYPE	11 C P U - 4 TYPE	Price EURO
GPC® 114		GPC® 68HC11A1 8 MHz; 32K SRAM, RS 232, RTC+Lithium, RS 232	171,72
<i>Option</i>	.BAS-114	EPROM BASIC for GPC® 114	17,86
<i>Option</i>	.8EE-114	OPTION 8K EEPROM for GPC® 114----->	15,31
<i>Option</i>	.32EE-114	OPTION 32K EEPROM for GPC® 114----->	19,55
<i>Option</i>	.WM4	OPTION BLOCK - Housing 50 mm for 4 Type GPC®	19,55
<i>Option</i>	.Ext-WM4	OPTION Extension BLOCK + 50 mm Extension Housing for 4 Type GPC®	6,8
<i>Option</i>	.LITIO	OPTION External LITHIUM Battery 2,1 A/H, with cable and connector	17,86
<i>Option</i>	.RS422	OPTION RS 422 SERIAL COMMUNICATION, Add --->	14,45

Option	.RS485	OPTION RS 485 SERIAL COMMUNICATION, Add-->	8,49
GPC® 154		GPC® 84C15; 10 MHz; 128K SRAM, 24C04 ser. EE+RTC+Lith., RS 232	219,35
GPC® 154.512K		GPC® 84C15; 10 MHz; 512K SRAM, 24C04 ser. EE+RTC+Lith., RS 232	255,06
Option	.WM4	OPTION BLOCK - Housing 50 mm for 4 Type GPC®	19,55
Option	.Ext-WM4	OPTION Extension BLOCK + 50 mm Extension Housing for 4 Type GPC®	6,8
Option	.FGD-154	FLASH-EPROM with GDOS-flash for GPC® 154 Add --->	23,8
Option	.512K	OPTION 512KRAM Add ----->	35,71
Option	.LITIO	OPTION External LITHIUM Battery 2,1 A/H, with cable and connector	17,86
Option	.EE-08	OPTION Serial EEPROM 24C08 ----->	3,4
Option	.EE-16	OPTION Serial EEPROM 24C16 ----->	6,8
Option	.EE-64	OPTION Serial EEPROM 24C64----->	16,15
Option	.RS422	OPTION RS 422 SERIAL COMMUNICATION, Add --->	14,45
Option	.RS485	OPTION RS 485 SERIAL COMMUNICATION, Add-->	8,49
GPC® 184		GPC® Z195; 22 MHz; 128K SRAM, 24C04 ser. EE+RTC+Lith., RS 232	201,49
GPC® 184.512K		GPC® Z195; 22 MHz; 512K SRAM, 24C04 ser. EE+RTC+Lith., RS 232	237,2
Option	.WM4	OPTION BLOCK - Housing 50 mm for 4 Type GPC®	19,55
Option	.Ext-WM4	OPTION Extension BLOCK + 50 mm Extension Housing for 4 Type GPC®	6,8
Option	.FGD-184	FLASH-EPROM with GDOS-flash for GPC® 184 Add --->	23,8
Option	.512K	OPTION 512KRAM Add ----->	35,71
Option	.LITIO	OPTION External LITHIUM Battery 2,1 A/H, with cable and connector	17,86
Option	.EE-08	OPTION Serial EEPROM 24C08 ----->	3,4
Option	.EE-16	OPTION Serial EEPROM 24C16 ----->	6,8
Option	.EE-64	OPTION Serial EEPROM 24C64----->	16,15
Option	.RS422	OPTION RS 422 SERIAL COMMUNICATION, Add --->	14,45
Option	.RS485	OPTION RS 485 SERIAL COMMUNICATION, Add-->	8,49
Option	.CLOOP	Option CURRENT LOOP Serial Communication, Add --->	31,46
GPC® 324		GPC® 80C32 (22 MHz) 32K SRAM, 24C04 ser. EE, RS 232	164,09
GPC® 324.FMO53		GPC® 80C32 (22 MHz) 32K RAM, E2 Seriale, + FMO53, RS 232	180,23
GPC® 324.BAS		BASIC, 80C32 (22 MHz) 32K SRAM, E2 Seriale, BASIC-52, RS 232	180,23
Option	.FMO53-324	OPTION EPROM FMO53 80C32 22 MHz----->	16,15
Option	.BAS-324	OPTION EPROM BASIC 80C32 22 MHz----->	16,15
Option	.LW-324	OPTION EPROM LadderWORK 80C32 22 MHz----->	16,15
Option	.WM4	OPTION BLOCK - Housing 50 mm for 4 Type GPC®	19,55
Option	.Ext-WM4	OPTION Extension BLOCK + 50 mm Extension Housing for 4 Type GPC®	6,8
Option	.32K	OPTION 32KRAM Add ----->	8,49
Option	.32KMOD	OPTION 32KRAM Backed Module, Add ----->	29,77
Option	.32KF	OPTION 32K FLASH Add ----->	17
Option	.32EE	OPTION 32K EEPROM for 80C32----->	19,55
Option	.LITIO	OPTION External LITHIUM Battery 2,1 A/H, with cable and connector	17,86
Option	.EE-08	OPTION Serial EEPROM 24C08 ----->	3,4
Option	.EE-16	OPTION Serial EEPROM 24C16 ----->	6,8
Option	.EE-64	OPTION Serial EEPROM 24C64----->	16,15
Option	.RS422	OPTION RS 422 SERIAL COMMUNICATION, Add --->	14,45
Option	.RS485	OPTION RS 485 SERIAL COMMUNICATION, Add-->	8,49
Option	.CLOOP	Option CURRENT LOOP Serial Communication, Add --->	31,46
GPC® 324D		GPC® 80C320 (22 MHz) 32K SRAM, 24C04 ser. EE, RS 232	196,38
GPC® 324D.FMO53		GPC® 80C320 (22 MHz) 32K RAM, E2 Seriale, + FMO53, RS 232	223,6
GPC® 324D.BAS		BASIC, 80C320 (22 MHz) 32K SRAM, 24C04 ser. EE, RS 232	223,6
Option	.FMO53-324D	OPTION EPROM FMO53 80C320 22 MHz----->	27,22
Option	.BAS-324D	OPTION EPROM BASIC for 80C320 22 MHz----->	27,22
Option	.LW-324D	OPTION EPROM LadderWORK 80C320 22 MHz----->	27,22
Option	.WM4	OPTION BLOCK - Housing 50 mm for 4 Type GPC®	19,55
Option	.Ext-WM4	OPTION Extension BLOCK + 50 mm Extension Housing for 4 Type GPC®	6,8

Option	.32K	OPTION 32KRAM Add ----->	10,2
Option	.32KMOD	OPTION 32KRAM Backed Module, Add ----->	29,77
Option	.32KF/D	OPTION 32K FLASH Add ----->	21,25
Option	.32EE/D	OPTION 32K EEPROM for 80C320 22MHz ----->	34,02
Option	.LITIO	OPTION External LITHIUM Battery 2,1 A/H, with cable and connector	17,86
Option	.EE-08	OPTION Serial EEPROM 24C08 ----->	4,25
Option	.EE-16	OPTION Serial EEPROM 24C16 ----->	6,8
Option	.EE-64	OPTION Serial EEPROM 24C64----->	16,15
Option	.RS422	OPTION RS 422 SERIAL COMMUNICATION, Add --->	14,45
Option	.RS485	OPTION RS 485 SERIAL COMMUNICATION, Add--->	8,49
Option	.CLOOP	Option CURRENT LOOP Serial Communication, Add --->	31,46
GPC® 554		GPC® 80C552 (22 MHz) 32K SRAM, 24C04 ser. EE, RS 232	155,58
GPC® 554.FMO53		FMO53, 80C552 (22 MHz) 32K SRAM, 24C04 ser. EE, RS 232	168,34
GPC® 554.BAS		BASIC, 80C552 (22 MHz) 32K SRAM, 24C04 ser. EE, RS 232	168,34
Option	.FMO53-554	OPTION EPROM FMO53 80C552 22 MHz----->	12,75
Option	.BAS-554	OPTION EPROM BASIC 80C552 22 MHz----->	12,75
Option	.LW-554	OPTION EPROM LadderWORK GPC® 554 ----->	12,75
Option	.WM4	OPTION BLOCK - Housing 50 mm for 4 Type GPC®	19,55
Option	.Ext-WM4	OPTION Extension BLOCK + 50 mm Extension Housing for 4 Type GPC®	6,8
Option	.8KRTC	OPTION 8K backed RAM Module with RTC also	37,4
Option	.32K	OPTION 32KRAM Add ----->	10,2
Option	.32KMOD	OPTION 32KRAM Backed Module, Add ----->	29,77
Option	.32KF	OPTION 32K FLASH Add ----->	17
Option	.32EE	OPTION 32K EEPROM for 80C552----->	19,55
Option.Vref/5	O E M	OPTION Vref. +5Vdc	8,49
Option	.LITIO	OPTION External LITHIUM Battery 2,1 A/H, with cable and connector	17,86
Option	.EE-08	OPTION Serial EEPROM 24C08 ----->	4,25
Option	.EE-16	OPTION Serial EEPROM 24C16 ----->	6,8
Option	.EE-64	OPTION Serial EEPROM 24C64----->	16,15
GPC® 884		GPC® 80C188ES (26 MHz) 128K SRAM, 24C04. RTC, A/D, RS 232	219,35
GPC® 884.512K		GPC® 80C188ES (26 MHz) 512K SRAM, 24C04. RTC, A/D, RS 232	255,06
GPC® 884/40		GPC® 80C188ES (40 MHz) 128K SRAM, 24C04. RTC, A/D, RS 232	264,4
GPC® 884/40.512K		GPC® 80C188ES (40 MHz) 512K SRAM, 24C04. RTC, A/D, RS 232	300,11
Option.FGD-884		FLASH-EPROM with GDOS-flash for GPC® 884 Add --->	23,8
Option.FWR-884		FLASH-EPROM with GCTR-flash for GPC® 884 Add --->	23,8
Option.FWR-884-512K		FLASH-EPROM with 512K GCTR-flash for GPC® 884 Add --->	32,31
Option.FGD-884/40		FLASH-EPROM with GDOS-flash for GPC® 884/40 Add --->	23,8
Option.FWR-884/40		FLASH-EPROM with GCTR-flash for GPC® 884/40 Add --->	23,8
Option.FWR-884/40-512K		FLASH-EPROM with 512K GCTR-flash for GPC® 884/40 Add --->	32,31
Option	.WM4	OPTION BLOCK - Housing 50 mm for 4 Type GPC®	19,55
Option	.Ext-WM4	OPTION Extension BLOCK + 50 mm Extension Housing for 4 Type GPC®	6,8
Option	.512K	OPTION 512KRAM Add ----->	35,71
Option	.LITIO	OPTION External LITHIUM Battery 2,1 A/H, with cable and connector	17,86
Option	.EE-08	OPTION Serial EEPROM 24C08 ----->	4,25
Option	.EE-16	OPTION Serial EEPROM 24C16 ----->	6,8
Option	.EE-64	OPTION Serial EEPROM 24C64----->	16,15
Option.Vref/5	O E M	OPTION Vref. +5Vdc	8,49
Option	.RS422	OPTION RS 422 SERIAL COMMUNICATION, Add --->	14,45
Option	.RS485	OPTION RS 485 SERIAL COMMUNICATION, Add--->	8,49
Option	.CLOOP	Option CURRENT LOOP Serial Communication, Add --->	31,46
GPC® AM4		ATMEL MEGA-103 (6 MHz) 32K SRAM, 128K Flash, 2K E2, RTC, A/D, F	181,94
Option	.WM4	OPTION BLOCK - Housing 50 mm for 4 Type GPC®	19,55
Option	.Ext-WM4	OPTION Extension BLOCK + 50 mm Extension Housing for 4 Type GPC®	6,8
Option	.LITIO	OPTION External LITHIUM Battery 2,1 A/H, with cable and connector	17,86

<i>Option</i>	.RS422	OPTION RS 422 SERIAL COMMUNICATION, Add --->	14,45
<i>Option</i>	.RS485	OPTION RS 485 SERIAL COMMUNICATION, Add--->	8,49
<i>Option</i>	.CLOOP	Option CURRENT LOOP Serial Communication, Add --->	31,46